SHELF LIFE OVERVIEW
SPECIALTY

The shelf life applies to unopened containers that are stored under normal storage conditions between 5-30°C / 41-86°F.

PRODUCT CODE	PRODUCT DESCRIPTION	SHELF LIFE
AD820	ADDITIVE TEXTURE FINE	2
AD830	ADDITIVE TEXTURE COARSE	2
AD850	ADDITIVE ELASTIFY	2
AD860	ADDITIVE ACCELERATOR	2
AD880	ADDITIVE MATTE	2
AD890	ADDITIVE MASKING	2
U9A1	ADDITIVE UNDERHOOD	1
U8FA1	FLOW ADDITVE	5
U9A2	BOOSTER	2

© 2022 The Sherwin-Williams Company

SHELF LIFE OVERVIEW
PRIMERS / SURFACERS

The shelf life applies to unopened containers that are stored under normal storage conditions between 5-30°C / 41-86°F.

PRODUCT CODE	PRODUCT DESCRIPTION	SHELF LIFE
P30A	PRIME 2K SURFACER - GRAY	2
P30B	PRIME 2K SURFACER - BLACK	2
P30W	PRIME 2K SURFACER - WHITE	2
P520A	PRIME STANDARD - GRAY	2
P520B	PRIME STANDARD - BLACK	2
P520W	PRIME STANDARD - WHITE	2
P530A	PRIME PRODUCTION NS - GRAY	2
P530B	PRIME PRODUCTION NS - BLACK	2
P530W	PRIME PRODUCTION NS - WHITE	2
P540A	PRIME UNIVERSAL - GRAY	2
P540B	PRIME UNIVERSAL - BLACK	2
P540W	PRIME UNIVERSAL - WHITE	2
P544A	PRIME DTM SPEED ELITE - GRAY	2
P544B	PRIME DTM SPEED ELITE - BLACK	2
P544W	PRIME DTM SPEED ELITE - WHITE	2
P580	PRIME PLASTIC ADHESION	3
P580	PRIME PLASTIC ADHESION SPRAY	5
P588	PRIME CORROSION PROTECTOR	2
P590B	PRIME SHADE BLACK	10
P590LG	PRIME SHADE LIGHT GRAY	10
P590MG	PRIME SHADE MID GRAY	10
P590W	PRIME SHADE WHITE	10
P599A	PRIME EPOXY - GRAY	2
P599W	PRIME EPOXY - WHITE	2
UVP1	PRIME UV SPRAY	2
UVP1	PRIME UV	2
UVP2	PRIME 1K UV	2

© 2022 The Sherwin-Williams Company

SHELF LIFE OVERVIEW
BODY FILLERS

The shelf life applies to unopened containers that are stored under normal storage conditions between 5-30°C / 41-86°F.

PRODUCT CODE	PRODUCT DESCRIPTION	SHELF LIFE
UB225	BODY FILLER UNIVERSAL	1
UB245	BODY FILLER SPRAY	1
UB230	BODY FILLER FIBREGLASS	1
UB235W	BODY FILLER HB - WHITE	1
UB235A	BODY FILLER HB - GRAY	1
UB240	BODY FILLER ALUMINIUM	1

© 2022 The Sherwin-Williams Company

SHELF LIFE OVERVIEW
CLEARS

The shelf life applies to unopened containers that are stored under normal storage conditions between 5-30°C / 41-86°F.

PRODUCT CODE	PRODUCT DESCRIPTION	SHELF LIFE
CC120	CLEAR SPEED SR	2
CC130	CLEAR MULTI DRY	2
CC133	CLEAR PRODUCTION	2
CC140	CLEAR ELITE GLOSS	2
CC144	CLEAR SPEED ELITE	1
CC154	CLEAR MATTE REPAIR LG	2
CC156	CLEAR MATTE REPAIR SG	2
CC166	CLEAR SPEED	2

© 2022 The Sherwin-Williams Company

SHELF LIFE OVERVIEW
ACTIVATORS

The shelf life applies to unopened containers that are stored under normal storage conditions between 5-30°C / 41-86°F.

PRODUCT CODE	PRODUCT DESCRIPTION	SHELF LIFE
AC15	ACTIVATOR TC1 MEDIUM	2
AC23	ACTIVATOR EXTRA SHORT	1
AC24	ACTIVATOR SHORT	1
AC25	ACTIVATOR MEDIUM	2
AC26	ACTIVATOR LONG	2
AC33	ACTIVATOR PRODUCTION SHORT	1
AC34	ACTIVATOR PRODUCTION LONG	1
AC44	ACTIVATOR SPEED ELITE	2
AC55	ACTIVATOR MATTE REPAIR	2
AC66	ACTIVATOR SPEED	2
AC88	ACTIVATOR CORROSION PROTECTOR	2
AC99	ACTIVATOR EPOXY	2
U9A44	ACTIVATOR WB SPEED ELITE	2
UH80	ACTIVATOR AIR DRY FULL BAKE	2

© 2022 The Sherwin-Williams Company

SHELF LIFE OVERVIEW
REDUCERS

The shelf life applies to unopened containers that are stored under normal storage conditions between 5-30°C / 41-86°F.

PRODUCT CODE	PRODUCT DESCRIPTION	SHELF LIFE
CL710	CLEAN SURFACE WATER	5
CL720	CLEAN GUN WATER	5
CL770	CLEAN DEGREASE	5
CL790	CLEAN SURFACE SOLVENT	5
R01	REDUCE PRIME UV	2
R14	REDUCE TC1 SHORT	2
R15	REDUCE TC1 MEDIUM	5
R16	REDUCE TC1 LONG	5
R24	REDUCE SHORT	5
R25	REDUCE MEDIUM	5
R26	REDUCE LONG	5
R27	REDUCE EXTRA LONG	2
R28	REDUCE EXTREMELY LONG	5
R30	REDUCE DISSOLVER	5
R30	REDUCE DISSOLVER SPRAY	10
R40	REDUCE BLENDING	5
R50	REDUCE POTLIFE EXTENDER	2
R55	REDUCE MATTE REPAIR	5
SR15	REDUCE SPEED	2
U9R1	REDUCE STANDARD	5

© 2022 The Sherwin-Williams Company