



# OneCure™

TWO COATS. ONE CURE. ZERO COMPROMISES.

## ZINC-RICH PRIMER

**OneCure is the industry's widest portfolio of dust-on-dust powder coating systems.**

Trusted by top OEMs for over a decade, OneCure's patented formula co-reacts and crosslinks primer and topcoat layers without the need to gel or cure the primer, resulting in significant cost savings, increased efficiency and speed.

**SHERWIN-WILLIAMS®**

Learn more at [onecure.oem.sherwin.com](https://onecure.oem.sherwin.com)

1-21-26\_acc [Accessibility Statement](#)



### THE OneCure ZINC-RICH EPOXY SYSTEM

The OneCure Zinc-Rich Epoxy powder coating system from Sherwin-Williams consists of a Zinc-Rich Epoxy Primer with a Superdurable Polyester Topcoat that can be applied with a single cure cycle, resulting in significant cost savings. This system is an excellent choice for OEMs with the most rigorous performance specifications in markets such as transportation, energy and more.

### MAXIMIZE CORROSION RESISTANCE, MINIMIZE TOTAL APPLIED COSTS

Specially formulated for the most demanding applications, the OneCure Zinc-Rich Epoxy system delivers:

- Best-in-class corrosion protection
- Outstanding chip resistance
- Exceptional edge coverage
- A wide range of color, gloss and texture options



In addition to its durable long-term performance, this patented system eliminates the intermediate cure step between primer and topcoat, providing the following paint process advantages:

- Significantly reduces cycle time compared to traditional two-layer powder systems
- Eliminates capital and operational expenses associated with a second oven, conveyor and cooling equipment
- Reduces footprint dedicated to designated part finishing areas
- Reduces work-in-process inventories

### OneCure Zinc-Rich Epoxy Primer and Superdurable Polyester Topcoat

TOP COAT	SALT SPRAY	CYCLIC CORROSION	QUVA GLOSS RETENTION	XENON ARC GLOSS RETENTION	PENCIL HARDNESS	GRAVELOMETER	OIL IMMERSION	GASOLINE IMMERSION	DIESEL IMMERSION
Superdurable TGIC Polyester	4,500 hrs	40 Cycles	90% @ 2,000+ hrs	90% @ 2,000+ hrs	3H+	6A/6B+	500+ hrs @ 25°C	72+ hrs @ 25°C	500+ hrs @ 25°C
Superdurable TGIC-Free Polyester	4,500 hrs	40 Cycles	90% @ 2,000+ hrs	90% @ 2,000+ hrs	2H+	6A/6B+	500+ hrs @ 25°C	72+ hrs @ 25°C	500+ hrs @ 25°C

At Sherwin-Williams, we think about coatings differently, continuously seeking the perfect solution to help your products win over your customers. Whether you need the most rugged and protective coating, a technical expert to provide answers and hands-on support, consistently perfect color at just the right gloss, or a custom solution created just for you – we are here to help. We are Sherwin-Williams General Industrial Coatings, and we are obsessed with giving you the competitive edge.