

**FIRETEX FX7002 APPROVED TOPCOATS**

**B59WW7002**

Architectural Topcoats	DFT (Mils)
ProMar® 400 Zero VOC	1.0 - 2.0
ProMar® 200 Zero VOC / HP	1.0 - 2.0
SuperPaint® Series	1.0 - 2.0
Duration Home®	1.0 - 2.0
Emerald® / Designer Addition™	1.0 - 2.1
Captivate™	1.0 - 2.0
Pro-Industrial™ Waterborne Acrylic Dryfall	3.0 - 5.0
Pro-Industrial™ Pro-Cryl® Waterbased Primer w/ Sher-Loxane® 800	2.0 - 4.0
Pro-Industrial™ Pro-Cryl® Waterbased Primer w/ Macropoxy® 646	2.0 - 4.0
High Performance Topcoats	DFT (Mils)
Pro-Industrial™ Pre-Catalyzed Epoxy	1.5 - 2.5
Pro-Industrial™ Multi-Surface Acrylic	1.5 - 2.5
Pro-Industrial™ Waterbased Catalyzed Epoxy	2.0 - 5.0
Pro-Industrial™ Acrylic	2.5 - 5.0
Pro-Industrial™ DTM Acrylic	2.4 - 4.0
Pro-Industrial™ W/B Acrolon 100	2.0 - 4.0
Acrolon® 218 Polyurethane	3.0 - 6.0
Hi-Solids Polyurethane / 250 Series	3.0 - 5.0
Acrolon® Ultra Polyurethane	2.0 - 3.0

A topcoat is not UL/ULC required for Interior Conditioned Space (ICS) areas.