SHERWIN WILLIAMS | HIGH PERFORMANCE FLOORING

FASTOP® TG SR

HEAVY-DUTY POLYURETHANE CEMENT FLOORING



R13 slip resistance | **-40°C to +120°C at 9mm** | **12-16 hrs light traffic at 20°C**

MAKE WET-PROCESS FLOORS SAFER, TOUGHER AND FASTER TO RETURN TO SERVICE

Highly slip-resistant flooring for demanding wet-process environments.

FasTop TG SR is a highly slip-resistant, very heavy-duty polyurethane cement floor screed engineered for aggressive wet-process areas. It combines R13 slip resistance with resistance to chemicals, abrasion, impact, hot water, steam and thermal shock, helping facilities improve safety, reduce disruption and extend flooring service life.

BUILT FOR THE TOUGHEST CONDITIONS

- Excellent resistance to chemicals, abrasion and heavy impact
- Resistant to hot water, steam cleaning and thermal shock
- Impermeable, non-porous and non-dusting matt finish
- Suitable for wet and dry environments, including freezers
- Very low emissions and water-based formulation
- Antimicrobial finish helps minimise microbial growth
- Can be applied to concrete from seven days old, subject to substrate requirements

IDEAL ENVIRONMENTS

- Food and beverage manufacturing
- Meat, poultry and seafood processing
- Pharmaceutical processing and wash bays
- Chemical production, blending and storage
- Heavy-duty plant and high-traffic areas

SYSTEM AT A GLANCE

Technology	Polyurethane cement screed
Finish	Matt, highly slip-resistant
Typical thickness	6–9 mm
Hot intermittent spillages	Up to 150°C at 12 mm
Application	Trowel
Primer	FasTop Multi Primer (optional)
FeRFA category	Type 8
Reaction to fire	Bfl-s1

FOOD-SAFE PERFORMANCE

Food safety compliance and non-taint: HACCP and Campden BRI approved for food manufacturing use.

HACCP INTERNATIONAL FOOD SAFETY PROGRAMME CERTIFICATION

Members of Campden BRI

EMISSION CLASS FOR BUILDING MATERIAL · RTS · M1

INDOOR AIR COMFORT eurofins GOLD CERTIFIED PRODUCT

THE SHERWIN-WILLIAMS DIFFERENCE

Sherwin-Williams High Performance Flooring delivers world-class industry subject matter expertise, unparalleled technical and specification service, and unmatched regional commercial team support to our customers around the globe.

resinflooring.sherwin.eu

FIND YOUR LOCAL CONTACT

10.26 HPF0184/02